

FSC-C024 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. One kinds of elastic ring provided:Ø15mm. Ø15 can be shrunk till Ø7.
2. The fittings provided with FSC-C024: 2 pieces of special wrench, earthing wire, nylon tie, labeling paper, desiccant, 4pcs of elastic ring, 4pcs of plastic gaskets.
3. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for bunchy or ribbon fiber, 1 piece metal hoop.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-C024I (bunchy)	460x190	96	4	16mm	OFST with 24 cores(1~4pcs of OFST 024)
FSC-C017II (ribbon)	mm	144			OFST with 36cores(1~4pcs of OFST 017)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC