

## FSC-E031 Closure

### Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



[www.youfibercable.com](http://www.youfibercable.com)

### Description

1. FSC-E031 accommodates one set of elastic seal fitting for 6 inlet/outlet ports.
2. Installation accessories provided: seal tape, insulation tape, 2pcs of special wrenches, abrasive cloth, earthing wire, nylon ties, labeling paper, measuring paper and desiccant.
3. Accessories by customers' selection: earthing device, buffer pipe, pressure testing valve, adapter panel, adapter, pigtail, patchcord, wall-mounting bracket and pole mounting bracket.

### Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Adapter and holes of Front Panel
FSC-E 031	490x220 mm	1-6pcs of 031# tray with 12pcs of cores per tray  1-4pcs of 032# tray with 24pcs of cores per tray	max6	2×Ø21mm 4×Ø16mm	1-4pcs of adapter panel, each can accommodate 6 FC adapters
					1-3pcs of adapter panel, each can accommodate 8 SC adapters
					1-3pcs of adapter panel, each can accommodate 8 ST adapters
					1-3pcs of adapter panel, each can accommodate 8 LC adapters

### Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC